

## Surface-mounted door station, 3-gang



| Specification                                                                                        | Order No. | Packing unit | PS | EAN           |
|------------------------------------------------------------------------------------------------------|-----------|--------------|----|---------------|
|  Pure white         | 1267 66   | 1            | 18 | 4010337267669 |
|  anthracite       | 1267 67   | 1            | 18 | 4010337267676 |
|  colour aluminium | 1267 65   | 1            | 18 | 4010337267652 |

## Features

- Fully pre-assembled surface-mounted door station for vertical surface-mounted installation. This allows quick and clean installation.
- In the design of the Gira TX\_44 design line.
- Torsionally rigid surface-mounted housing thanks to aluminium profile.
- Frame made of shatter-proof thermoplastic with high resistance to ultraviolet light as well as a scratch-resistant, care-free surface.
- Theft protection by means of Torx screws.
- Signal transmission and supply of the audio and video components via reverse-polarity-protected and short-circuit-proof 2-wire bus.
- One-man start-up with easy start-up procedure.
- Weather-resistant speaker.
- High-quality electret microphone.
- Speakerphone function (voice-controlled talk-back with echo and background noise suppression).
- Audible acknowledgement signal when a call button is pressed.
- Adjustable voice volume.
- White call-button illumination in LED technology. Even, clearly visible call button illumination is achieved via maintenance-free, energy-saving LED technology.
- Sprayed-water proof call-button cover plate made of shock-resistant plastic.
- Name plate of the call button can be exchanged without tools and without frame disassembly.
- Professional labelling is available from the Gira Inscription Service [www.marking.gira.com](http://www.marking.gira.com) or using the Gira inscription software.
- Low profile height of just 19 mm.

## Technical data

|               |                    |
|---------------|--------------------|
| Power supply: | via the 2-wire bus |
| Connections   |                    |
| - 2-wire bus: | 2x screw terminals |

Illustrations are similar and may deviate from originals.

- Additional power supply: 2x screw terminals

Protection type: IP44

Ambient temperature: -25 °C to +70 °C

---

## Notes

- Call buttons which are not required can be covered with the call-button cover plate for call button, 3-gang.

---

## Dimensions in mm

|              |       |       |      |
|--------------|-------|-------|------|
| Name plates: | W 110 | H 181 | D 19 |
|              | W 62  | H 18  | D -  |