



**EAN:** 4013288228338  
**Part number:** 05075851001  
**Article number:** 7515/16

**Size:** 175x125x60 mm  
**Weight:** 609 g  
**Country of origin:** CZ  
**Customs tariff number:** 82079030

- Torque screwdriver with quick torque adjustment
- Easy and quick torque setting
- Fixed position (Torque Lock) for unlimited tightening and loosening moments
- Secure slip-over torque function for clockwise/anti-clockwise torque-control
- Quick and easy setting of the selectable tightening torques (2.0; 3.0; 4.0; 5.0; 6.0 Nm)
- For bits with 1/4" external hexagon drive, also suitable for socket wrench inserts via adapter - ideal for bike operations
- Tools with Hex-Plus profile prevent premature rounding of hexagonal socket screws
- Suitable for docking with the Wera 2go system

16-piece tool set. For professional screwdriving/professional fine adjustment AND for torque-controlled screwdriving. Secure slip-over torque mechanism with quick clockwise/counterclockwise setting and five selectable tightening torques (2.0; 3.0; 4.0; 5.0; 6.0 Nm) and one fixed position (Torque Lock) for unlimited loosening and tightening moments. Quick-release holder for high robustness. Suitable for bits with 1/4" external hexagon drive. 15 tough bits (89 mm length).



### Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraftform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7515\\_16.html](https://products.wera.de/en/torque_tools_series_7500_kraftform_safe-torque_speed_torque_screwdrivers_null_7515_16.html)

Wera - 7515/16  
05075851001 - 4013288228338

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**Five selectable tightening torques**



Torque screwdriver with quick torque adjustment



Five selectable tightening torques (2.0; 3.0; 4.0; 5.0; 6.0 Nm) and one fixed position (Torque Lock) for unlimited tightening and loosening moments.

**Simple setting**



Easy setting of the selectable tightening torques.

**Excess-load signal**




Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

**Storage and transport**



Storage and transport in a robust and compact textile roll bag, so the tool is always close at hand.

**Flexible thanks to hook and loop fastener strips**



The textile box features a fleece zone at the back. Using the provided self-adhesive hook and loop fastener strips, the textile box can be attached to the Wera 2go components. Or to the wall, shelf or workshop trolley.

**Web link**

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraftform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7515\\_16.html](https://products.wera.de/en/torque_tools_series_7500_kraftform_safe-torque_speed_torque_screwdrivers_null_7515_16.html)

Wera - 7515/16  
05075851001 - 4013288228338

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

## 7515/16 Kraftform Safe-Torque Speed Universal 1, 16 pieces

### Series 7500 Kraftform Safe-Torque Speed Torque Screwdrivers -



#### Set contents:

#### 7515 Kraftform Safe-Torque Speed Torque screwdriver, 2-6 Nm, 1/4" x 2.0 Nm x 3.0 Nm x 4.0 Nm x 5.0 Nm x 6.0 Nm x 147.5 mm

05075815001 1x 1/4" x 2.0 Nm x 3.0 Nm x 4.0 Nm x 5.0 Nm x 6.0 Nm x 147.5 mm



#### 851/4 Z bits, PH 2 x 89 mm



05059775001 1x PH 2 x 89 mm



#### 867/4 Z TORX® B0 bits with bore hole, TX 10 x 89 mm



|             |                  |
|-------------|------------------|
| 05060050001 | 1x TX 10 x 89 mm |
| 05060051001 | 1x TX 15 x 89 mm |
| 05060052001 | 1x TX 20 x 89 mm |
| 05060053001 | 1x TX 25 x 89 mm |
| 05060054001 | 1x TX 30 x 89 mm |



#### 867/4 IP TORX PLUS® bits, 10 IP x 89 mm



|             |                  |
|-------------|------------------|
| 05134671001 | 1x 10 IP x 89 mm |
| 05134672001 | 1x 15 IP x 89 mm |
| 05134673001 | 1x 20 IP x 89 mm |
| 05134674001 | 1x 25 IP x 89 mm |
| 05134676001 | 1x 30 IP x 89 mm |



#### 840/4 Z bits, 3 x 89 mm



|                           |              |
|---------------------------|--------------|
| 05059630001               | 1x 3 x 89 mm |
| 05059631001               | 1x 4 x 89 mm |
| 05059632001               | 1x 5 x 89 mm |
| 05059633001 <sup>1)</sup> | 1x 6 x 89 mm |



1) Hexagonal blade

#### Web link

[https://products.wera.de/en/torque\\_tools\\_series\\_7500\\_kraftform\\_safe-torque\\_speed\\_torque\\_screwdrivers\\_null\\_7515\\_16.html](https://products.wera.de/en/torque_tools_series_7500_kraftform_safe-torque_speed_torque_screwdrivers_null_7515_16.html)

Wera - 7515/16  
05075851001 - 4013288228338

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)