



MP-B20 SERIES MOBILE PRINTER



Seiko Instruments super small and affordable 2" mobile printer meets the trend towards greater mobility. The MP-B20 Series Mobile Printers support Bluetooth[®] connectivity and are compatible with the latest operating systems including Windows[®], Android[™] and iOS[®].

"Made for iPod", "Made for iPhone", "Made for iPad" mean that an electronic accessory has been designed to connect specifically to iPod, iPhone and iPad respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

MP-B20 SERIES

Mobile Printer

- Very small and lightweight
- Withstand drops from up to 1,5 meters
- USB style battery charger
- 80mm/s printing speed
- Color option: Black, White
- optional cradle

MP-B20
Cradle option



Measuring
Instrument



PDA/
Smart Device



Barcode



Portable
Printer



Medical
Equipment

Model		MP-B20
Printing	Method	Thermal line dot printing
	Number of dots/line	384
	Resolution (dots/mm)	8
	Paper width (mm)	58 ⁺⁰ ₋₁
	Printing width (mm)	48
	Speed (mm/sec) max	80
	Outside diameter of paper roll (mm) max	Ø 40
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of Paper		Roll paper
Character type		Code page(17 pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Bar code		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128 PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply (V)		Li-Ion Battery
Communication interface		USB, Bluetooth®
Input buffer		4K bytes
Command		ESC/POST™ conformity
Cutting		Tear bar
Falling resistance		1.5m* ¹
Operating temperature (°C)		-10 to 50
Service life (km)		50* ²
Dimensions (W×D×H mm)		79.0 × 110.0 × 44.0* ³
Mass (g)		Approx. 180* ⁴
Standard		FCC, CE, VCCI
Bundled item		USB cable, Battery, Belt clip
Option		Cradle for charging
Software		Printer driver, Windows®, Android™(SDK), iOS(SDK)

*1 This number is test result based on SII procedures, not guaranteed value. *2 using specified thermal paper *3 Excluding protrusion *4 with battery, without paper roll

ESC/POST™: Registered trademark of SEIKO EPSON CORP.
Windows® is the registered trademark of Microsoft Corporation(USA).

Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.



Seiko Instruments GmbH
phone: +49-6102-297-100
info@Seiko-Instruments.de
www.seiko-instruments.de

SEIKO
SEIKO HOLDINGS GROUP