

HVE-6701T, HDMI over IP PoE Transmitter (T), 150 Meter

Product Images



Short Description

- Flexible and scalable HDMI 1080p High Quality Video Broadcasting with Gigabit Ethernet LAN.
- Support Transmission distance Point-to-Point up to 150 Meter.
- Support Point-to-Point, Point-to-Many and Many-to-Many network configuration.
- Built-in Button switch to change Group ID.
- Transmits an HDMI signal over one CAT5e/6/7 cable.
- Transmits HDTV resolutions up to 1080p.
- HDMI 1.3b and HDCP compliant.
- Support powered by VDC 12V or PoE.

Description

The LevelOne HVE-670 Series is an innovative HDMI-over-IP Distribution Solution.

Designed with transmitting units (HVE-6701T) and receiving units (HVE-6701R), it offers scalable digital signage distribution, supporting HDMI 1.3 with 1080p video resolution and simultaneous audio broadcast.

The HVE-670 Series enriches HDMI signal broadcasting connectivity options from small scaled home theatres, retail stores, up to large scaled public premises such as transportation hubs, leisure educational facilities, corporate premises and more. Powerful Distribution Capabilities The pioneering LevelOne HVE-670 system expands HD digital content reachability.

Allowing multiple sources extend to more than 99 group displays in LAN without limit by cascading managed switches.

The solution is highly flexible that Point-to-Point or Point-to-Many topologies could be conveniently arranged. And to meet wider range of application requirement, HVE-670 Series offers options to be powered by PoE or external power supplying unit. Additionally, video sources could be distributed per preset display group via easily hardware adjustment of Button .

Additional Information

Harmonized System (HS) code	854370
Color	Black
EAN	4015867239056
Model Number	HVE-6701T
Approval and Compliance	CE/FCC
Operating humidity	5% RH ~ 90% RH
Operating temperature	-5°C ~ 55°C
Package Contents	Power adapter QIG IR(T)
Port Configuration	HDMI, IR(3.5mm),RS-232, RJ-45, Power ,USB 1.1 (Mini)
Power consumption	Max :3.3W
Power input	The power adapter: DC 12V POE input voltage range:36~57V
Power supply included	Yes
Resolution	1920*1080 @ 60 Hz
Standard	IR interface : 3.5mm IR Frequency :20-60KHz Power consumption: 3.3W
Video Bandwidth	Max Bandwidth :16 Mbps HDMI Bandwidth :Max 6.75Gbps /Max clock 165MHz
Dimensions (W x D x H)	119*81.7*23mm
Product weight (kg)	0.5

