

Vivolink VLSPSUB100 loudspeaker 2-way Wired 60 W

Brand : Vivolink

Product code: VLSPSUB100

Product name : VLSPSUB100

Active powered Subwoofer 8" 50W + 2x25W 2.1

Vivolink VLSPSUB100 loudspeaker 2-way Wired 60 W:

Vivolink Active Subwoofer is a perfect match to all Vivolink speakers. It is designed to be mounted over ceiling or under furniture

Ideal for meeting rooms, hotels and auditoriums.

It have line input and loop out for active satellite speakers.

Subwoofer can also be used together with passive satellite speakers using the internal power amplifier for satellite speakers on 2 x 25W

- For rooms up to 200m²
- Power effect for subwoofer: 50 Watts
- Power effect for passive ceiling speakers: (VLSPMTC60WT) 2x25Watts
- Inputs: 100V, Balanced in and RCA line in
- Bluetooth input for speaker out only (not supported for line-out)
- Outputs: RCA line out and Speaker out 2x 25W
- Line out for active speakers (VLSP60/65/61/70)
- Frequency range: 80Hz-20kHz
- Impedance: 8 Ohm



Loudspeakers		Power	
Speaker type *	2-way	Power source type	AC
Audio output channels *	2.0 channels	AC input voltage	230 - 240 V
Speaker placement *	Wall-mountable	Power consumption (typical)	75 W
Number of drivers *	2	Power consumption (standby)	0.5 W
Tweeter diameter (imperial)	2.54 cm (1")	Current	1 A
Woofer diameter (imperial)	13.3 cm (5.25")	Weight & dimensions	
Audio		Width	178 mm
RMS rated power *	60 W	Depth	162 mm
Peak Music Power Output (PMPO)	300 W	Height	240 mm
Speakers RMS power	30 W	Weight	6.26 kg
Frequency range	45 - 20000 Hz	Cord length	10 m
Impedance	4 Ω	Packaging data	
Sensitivity	88 dB	Package width	440 mm
Performance		Package depth	210 mm
Recommended usage *	Universal	Package height	265 mm
Number of speakers *	2	Package weight	6.75 kg
Housing material	Plastic	Packaging content	
Volume control	Rotary	Cables included	AC
Certification	CE	Other features	
Ports & interfaces		Speaker weight	6.36 g
Connectivity technology *	Wired	Front speaker frequency range	45 - 20000 Hz
6.35 mm (1/4-inch) input	1	Front speaker impedance	4 Ω
Audio RCA inputs	1	Front speaker sensitivity	88 dB
Connector(s)	RCA, Minijack, Phoenix	Housing colour	White
		Power source	AC



5715063260494

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.