j5create

j5create JUCX05 USB-C® 3.1 to USB™ Type-A Adapter, White and Silver



Brand : j5create

Product code: JUCX05-N

Product name : JUCX05 USB-C® 3.1 to USB™ Type-A Adapter, White and Silver

- Small reversible connector
- High durability and versatility
- Built-in Electronically-Marked IC for USB™-IF Power Delivery 2.0 specifications
- Supports USB™ 2.0 (480 Mbps)

JUCX05 USB-C® 3.1 to USB Type-A Adapter, White and Silver

j5create JUCX05 USB-C® 3.1 to USB™ Type-A Adapter, White and Silver:



The JUCX05 USB-C® Cable is powerful and reversible, and there is no wrong way to plug it in. The USB-C® cable supports USB™ 2.0 with speeds up to 480 Mbps and an output of 5V and 3A. The cable will significantly cut down on the amount of wires needed to power devices. It is also compatible with USB™ 3.0 and USB™ 2.0 devices. The USB-C® cable is designed to work with existing USB™ devices j5create JUCX05 USB-C® 3.1 to USB™ Type-A Adapter, White and Silver. USB Power Delivery up to: 4.5 W. Product colour: Silver, White, Country of origin: Taiwan. Output voltage: 3 V. Width: 16 mm, Height: 8 mm, Weight: 12 g. Quantity per pack: 1 pc(s), Package width: 120 mm, Package depth: 97 mm

Ports & interfaces	
USB Power Delivery up to	4.5 W
Performance	
Product colour *	Silver, White
Plug and Play	✔
Country of origin	Taiwan
Power	
Output voltage	3 V
Software	
Windows operating systems supported	✔
Mac operating systems supported	✔
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Weight & dimensions	
Width	16 mm
Height	8 mm
Weight	12 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	120 mm
Package depth	97 mm
Package height	25 mm

Packaging data	
Package weight	45 g
Packaging content	
Packaging content	1 x JUCX05 USB-C® Cable
Technical details	
Box contents	1 x JUCX05 USB-C® Cable
Master (outer) case GTIN (EAN/UPC)	24712795080760
Warranty period	2 year(s)
Logistics data	
Products per master (outer) case	20 pc(s)
Master (outer) case width	280 mm
Master (outer) case length	210 mm
Master (outer) case height	145 mm
Master (outer) case gross weight	1.14 kg
Export Control Classification Number (ECCN)	EAR99
Other features	
Cable length	0.1 m
Maximum data transfer rate	5000 Mbit/s
Technical features	Simultaneously charge and sync your connected devices, High durability and versatility



0847626001178



847626001178



4712795080766



Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2026. Prints or copies of Information are only valid on the printed Publication date