

Vivolink VLEXTA170 AV extender AV transmitter & receiver Black

Brand : Vivolink

Product code: VLEXTA170

Product name : VLEXTA170

- 3 selectable audio inputs
 - Power over Cable (PoC), from Rx to Tx.
 - 100m audio transmission
 - 3 audio synchronized outputs
- Audio Extender Kit, with 12V/1A PSU EU plug

Vivolink VLEXTA170 AV extender AV transmitter & receiver Black:

VLEXTA170 is an audio extender, including transmitter & receiver. It distributes audio signal via CATx cable at 100m with PoC function from Rx to Tx.

It provides TOSLINK/COAX/STEREO audio inputs.

Vivolink VLEXTA170. Type: AV transmitter & receiver, Cable types supported: Cat5e, Maximum transfer distance: 100 m. Connectivity technology: Wired. AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz, Operating voltage (transmitter): 12 V. Width: 80 mm, Depth: 80 mm, Height: 21.5 mm. Package width: 156 mm, Package depth: 155 mm, Package height: 120 mm



Features		Power	
Type *	AV transmitter & receiver	Output current	1 A
Cable types supported	Cat5e	Operating voltage (receiver)	12 V
Maximum transfer distance	100 m	Power consumption (transmitter) (max)	2.5 W
Audio output channels	2.0 channels	Power consumption (receiver) (max)	2.5 W
IR pass-through	✓	External power adapter	✓
LED indicators	✓	Operational conditions	
Audio formats supported	PCM	Operating temperature (T-T)	-10 - 55 °C
HDCP & EDID bypass	✓	Operating relative humidity (H-H)	10 - 90%
Wall mountable	✓	Weight & dimensions	
Product colour	Black	Width	80 mm
Ports & interfaces		Depth	80 mm
Connectivity technology *	Wired	Height	21.5 mm
Wi-Fi	✗	Weight	240 g
Bluetooth	✗	Receiver dimensions (WxDxH)	88 x 80 x 21.5 mm
RJ-45 input ports	1	Transmitter dimensions (WxDxH)	88 x 80 x 21.5 mm
RJ-45 output ports	1	Packaging data	
Digital audio coaxial out	1	Package width	156 mm
Video in	1	Package depth	155 mm
Video out	1	Package height	120 mm
Audio (L/R) out	1	Package weight	484 g
Audio input	3	Packaging content	
Audio output	3	AC adapter included	✓
3.5 mm (1/8-inch) in	✓	Included power plug types	EU
3.5 mm (1/8-inch) out	✓	IR blaster included	✗
Audio RCA outputs	1	IR receiver included	✗
DC-in jack	✓	Mounting brackets included	✓

Power		Technical details	
AC input voltage	100 - 240 V	Audio support	✓
AC input frequency	50 - 60 Hz		
Operating voltage (transmitter)	12 V		



5711783853855

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.