DONN29G 6-in-1 USB 3.2 Gen 2 Docking Station, 4K60Hz HDMI, USB-A 10Gbps x 2, USB-C 10Gbps, GbE LAN, 140W USB PD 3.1

Product Images















Short Description

- 6-in-1 USB-C to HDMI/USB-C PD/USB-A (10Gbps)/USB-C (10Gbps)/GbE multiport adapter
- Supports HDMI resolutions up to 4K 60Hz
- Supports USB Power Delivery (PD) 3.1 up to 140W
- Provides a Gigabit Ethernet port with speeds up to 1000Mbps
- Supports Wake-on-LAN feature to startup computers remotely
- USB 3.2 Gen 2 SuperSpeed (10Gb/s)
- Multi-platform support: Windows, macOS, ChromeOS, Linux, Android, iOS
- Simple Plug and Play installation
- Cable length: 25cm
- Aluminum casing for heat dissipation

Description

This 6-in-1 Docking Station expands your device's USB Type-C functionality with HDMI, USB-C PD, USB-C (10Gbps), USB-A (10Gbps), and RJ45 ports. It's an ideal solution for MacBooks or Windows laptops with built-in wireless connectivity but no Ethernet port. Featuring a Gigabit Ethernet connection, it ensures fast and reliable wired network access. Additionally, the docking station supports up to 140W power delivery for compatible laptops or tablets with USB-C PD 3.1 support.

The docking station enables USB-C-compatible laptops, tablets, or smartphones to connect to an HDMI-enabled display, delivering stunning 4K Ultra HD resolution at a 60Hz refresh rate. With data transfer speeds of up to 10Gbps, it ensures stable and efficient performance, making it ideal for home entertainment, office presentations, and classroom teaching.

Additional Information

Harmonized System (HS) code	8471800000
Customs product code (TARIC)	8471800000
Approval and Compliance	CE, RoHS
Operating temperature	0°C ~ 45°C
Compatible operating systems	Windows XP/Vista/7/8/10/11 MacOS 10.5 or above Android 5.0 or above
Package Contents	DONN29G Multilingual quick installation guide
Cable Length	0.25m
Dimensions (W x D x H)	131.5 x 32.5 x 14 mm
Product weight (kg)	0.06
Color	Grey
EAN	4015867239629
Model Number	DONN29G
USB Power Delivery (PD)	140W
Bandwidth	10Gbps
Connector	USB-C male
Port Configuration	HDMI x 1, USB-A 10Gbps x 2, USB-C 10Gbps x 1, USB-C PD x 1, GbE x 1
Power supply included	No
Resolutions	4K 60Hz
Standards	IEEE 802.3ab 1000BASE-T, Gigabit Ethernet, HDMI 2.0, USB PD 3.1, USB 3.2 Gen 2

