



## ACT Powercord C20 - C21 IEC60320 red 2.5 m

**Brand :** ACT

**Product code:** AK5363

**Product name :** Powercord C20 - C21 IEC60320 red 2.5 m



- Cable length: 2.5 m
  - Connectors: C20 - C21 IEC60320
  - The C21 connector is high temperature resistant up to 155°C
  - Maximum load: 250V~/16A
  - Colour: red
  - Suitable for servers, network switches; e.g. HP and Cisco
- Powercord C20 - C21 IEC60320 red 2.5 m

### ACT Powercord C20 - C21 IEC60320 red 2.5 m:

The C20 to C21 powercord is used for powering high power equipment, such as servers from the most common used brands. The C21 connector is high temperature resistant up to 155°.

ACT provides many types of power cables: CEE 7/7, Euro, UK, USA, Italian, Danish, Swiss and South African cables. ACT supplies powercables with the following connectors: CEE 7/7, IEC60320 C5, C7, C13, C14, C15, C19, C20, C21 and IEC60309 CEE1. ACT offers different types of power split cables and power cables in the following colors: black, white, red, blue, green and yellow.

ACT Powercord C20 - C21 IEC60320 red 2.5 m. Cable length: 2.5 m, Connector 1: C20 coupler, Connector 2: C21 coupler. Input voltage: 250 V, Input current: 16 A



#### Features

|                         |                          |
|-------------------------|--------------------------|
| Product colour *        | Red                      |
| Connector 1 gender *    | Male                     |
| Connector 2 gender *    | Female                   |
| Cable length *          | 2.5 m                    |
| Connector 1 *           | C20 coupler              |
| Connector 2 *           | C21 coupler              |
| Connector 1 standard    | IEC 60320                |
| Connector 2 standard    | IEC 60320                |
| Connector 1 form factor | Straight                 |
| Connector 2 form factor | Straight                 |
| Jacket material         | Polyvinyl chloride (PVC) |

#### Features

|                         |                   |
|-------------------------|-------------------|
| Conductor material      | Copper            |
| Number of conductors    | 3                 |
| Conductor cross section | 1 mm <sup>2</sup> |

#### Power

|               |       |
|---------------|-------|
| Input voltage | 250 V |
| Input current | 16 A  |

#### Operational conditions

|                             |           |
|-----------------------------|-----------|
| Operating temperature (T-T) | 0 - 70 °C |
|-----------------------------|-----------|

#### Certificates

|                         |    |
|-------------------------|----|
| Compliance certificates | CE |
|-------------------------|----|

#### Packaging data

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|



8716065583649

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.